

Declaration of Performance

2 layer Style68 Meranti/Alu



DoP ref. S1682023-MA2

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 2 layer Style68 Meranti/Alu
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK, 5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance:
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 1,36
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK, 5260 Odense S
Denmark

23

DoP ref. S1682023-MA2
EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Style68 Meranti/Alu
Dedicated for use in residential and public buildings

Resistance to wind load: npd
Acoustic performance: npd
Thermal transmittance (U-value): 1,36
- Window outward opening 1230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf. +45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

2 layer Thermo80 Meranti



DoP ref. Th802023-M2

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 2 layer Thermo80 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 1,28
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. Th802023-M2
EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Thermo80 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load: npd

Acoustic performance: npd

Thermal transmittance (U-value): 1,28

- Window outward opening 1230x1480 mm standard glazing:

Radiation properties:

- Solar factor (gg-value): 0,63

- Light transmittance (LTg-value): 0,80

Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf. +45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

2 layer Thermo80 Meranti/Alu

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.


Product type: Windows and external pedestrian doorset
Identification: 2 layer Thermo80 Meranti/Alu
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK, 5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body:
EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 1,28
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

On behalf of the producer:


Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23

CE

JABS Group A/S
Kratholmvej 27B
DK, 5260 Odense S
Denmark

23

DoP ref. Th802023-MA2
EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Thermo80 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load: npd
Acoustic performance: npd
Thermal transmittance (U-value):
- Window outward opening 1230x1480 mm standard glazing: 1,28

Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Thermo80 Meranti

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Thermo80 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body:
EN 14351-1:2006 A2-2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: Passed
Load bearing capacity of safety devices: npd
Acoustic performance: npd
Thermal transmittance (U-value): 0,94
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

On behalf of the producer:



Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23

CE

JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. Th.802023-M3
EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Thermo80 Meranti
Dedicated for use in residential and public buildings

Resistance to wind load: npd
Acoustic performance: npd
Thermal transmittance (U-value):
- Window outward opening 1230x1480 mm standard glazing: 0,94

Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Thermo80 Meranti/Alu



DoP ref. Th802023-MA3

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Thermo80 Meranti/Alu
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK, 5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body:
EN 14351-1:2006 A2-2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 0,94
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK, 5260 Odense S
Denmark

23

DoP ref. Th802023-MA3
EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Thermo80 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load: npd
Acoustic performance: npd
Thermal transmittance (U-value): 0,94
- Window outward opening 1230x1480 mm standard glazing:

Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf. +45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Elite92 Meranti



DoP ref: EI922023-M3

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Elite92 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 0,84
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

On behalf of the producer:

Bo Ovegaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref: EI922023-M3
EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Elite92 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load: npd

Acoustic performance: npd

Thermal transmittance (U-value):

- Window outward opening 1230x1480 mm standard glazing: 0,84

Radiation properties:

- Solar factor (gg-value): 0,50

- Light transmittance (LTg-value): 0,71

Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Elite92 Meranti/Alu



DoP ref. E1922023-MA3

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Elite92 Meranti/Alu
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 0,84
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. E1922023-MA3
EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Elite92 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load: npd
Acoustic performance: npd
Thermal transmittance (U-value): 0,84
- Window outward opening 1230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,50
- Light transmittance (LTg-value): 0,71
Air permeability: npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

2 layer Style68 Meranti



DoP ref. St682023-M2

The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 2 layer Style68 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK, 5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3
Harmonized standard & Notified Body: EN 14351-1:2006 A2-2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance: npd
Resistance to wind load: npd
Watertightness: npd
Dangerous substances: npd
Load bearing capacity of safety devices: Passed
Acoustic performance: npd
Thermal transmittance (U-value): 1,36
- Window 230x1480 mm standard glazing:
Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK, 5260 Odense S
Denmark

23

DoP ref. St682023-M2
EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Style68 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load: npd

Acoustic performance: npd

Thermal transmittance (U-value):
- Window outward opening 1230x1480 mm standard glazing: 1,36

Radiation properties:
- Solar factor (gg-value): 0,63
- Light transmittance (LTg-value): 0,80
Air permeability: npd

npd: no performance determined
The actual values can be informed by contacting JABS Group A/S tlf. +45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.