



Declaration of performance

ESD/DOP-Nr.101

1. Product system	PVC Synego NL I ALPO NL
2. Application	Entrance doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Single sash Entrance door (20mm ALU threshold)**	Double sash Entrance door (20mm ALU threshold)***
Product ID	EFD	EDF
Product measurements	1176x2448	1196x2458
Air permeability (EN 12207)	4	4
Water tightness (EN 12208)	E750	5A
Wind resistance (EN 12210)	B4	B4
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*0.9	*0.86
Light transmission T_L , % (EN 410)	*73	*73
Solar energy transmission g , % (EN 410)	*53	*53
Acoustic performance (EN ISO 140-1:1997+A1:2004), R_w (C;C _{tr}) dB	-	-

* formula of glass panel (4XN-18ar (SWS)-4-18ar (SWS)-4 XN) – 3 layers of glass. Inner and outer glass with selective coating, middle glass is clear glass. Warm edge is included in gaps - Swisspacer (advanced), gaps are filled with argon gas – 90%.

** Doors opens to inside;

*** Doors opens to outside;

On behalf of manufacturer signed by:

Arturas Radzevičius

Product constructor-technologist

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895